

65-27  
#65-073

CONFIDENTIAL

25X1

25X1



25/66

9 September 1965

25X1



675-65WR.

Design and manufacture of the test apparatus for the best shock program is now under way. For testing of the apparatus and sensitometric assignment of the results, the following film will be required.

3 each 1000 ft rolls - 70 M/M Type 8430

3 each 1000 ft rolls - 70 M/M Negative S.O. 243 or 4404 as second choice.

I would appreciate your assistance in obtaining this material if at all possible.



25X1

IGR:mm

Declass Review by  
NIMA/DOD

This document contains information affecting the National Defense of the United States within the meaning of the Espionage Law, Title 18, U. S. C., Section 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

CONFIDENTIAL

GROUP - 1  
Excluded from  
Automatic  
downgrading and  
declassification

**CONFIDENTIAL**

65.28

65.072

C1 of 5

7604


25X1



8 September 1965

Please Reference:  
A51-65-3340

25X1



675-65WR

Our Sales Order 1-10290-1

Gentlemen:

We are pleased to provide the second in a series of Monthly Progress Reports covering the effort expended on subject contract during the period of August 2, 1965 to September 1, 1965.

Manpower

The group was strengthened by the addition of two senior personnel.

25X1



, Research Engineer.

Senior Research Engineer.

25X1

25

is a new hire, engaged to work on the film drying techniques program. is an existent member of the engineering staff who has been transferred to the research group to assist in the thermal shock studies.

25X1

Clean Room Installation

The changes to the clean room control equipment necessary to enable the requirements of Fed. Std. No. 209 - "Clean Room and Work Station Requirements, Controlled Environment" to be met, were completed, and a test conducted by an independent organization. The results of the test showed that an average particle content of 85 particles per cubic foot of

continued - - -

This document contains information affecting the National Defense of the United States within the meaning of the Espionage Law, Title 18, U. S. C., Section 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

**CONFIDENTIAL**

GROUP - 1  
Excluded from  
Automatic  
Downgrading and  
declassification

**CONFIDENTIAL**

U. S. Government

2

8 September 1965  
A51-65-3340

air: 50 microns or larger was obtained, thus exceeding the specification requirements. A copy of the report is enclosed. In the area of temperature and humidity control, changes to the control system and the humidification system were also completed, and a series of tests initiated. At the time of this report the relative humidity and temperature tests completed, showed that the systems were controlling within the specified tolerances. One test is outstanding, 85°F. at 45 percent R.H., but no difficulty is now anticipated in meeting this requirement. The final documents, the operating and maintenance instructions have been requested prior to signing off of the installation within the forthcoming week.

Future Programs

25X1 Recently, discussions were held with customer representatives at [ ] 25X1  
[ ] Proposals on the following equipment will be prepared and submitted. HTA/5. Film Processor, ABD4 Drier, Chip Processor. In preparation also by request, is a detailed breakdown of the requirements for an analytical study to determine the effect of contamination on photographic image quality and photographic interpretation. During this visit, a detailed briefing of other areas of research was given, including investigations conducted into dry film processing and printing. A descriptive precis of more than a dozen other areas of potential research was prepared for appraisal by the customer.

Included in this report are the results and/or status of the positive pressure transport capstan, intertank transfer bearing, rotary air and liquid bearing investigations, which have been curtailed at these points in order to concentrate the group efforts on the thermal shock, film drying and sensitometric studies. The new areas of the research program thermal shock and film drying are now under way with the literature search almost complete in both cases, and some preliminary experimental testing completed.

Research Program

## 1. Positive-Pressure Transport Capstan.

The preliminary performance evaluation of the Positive-Pressure Transport Capstan (recorded in Report 974-006-1) was essentially culminated and the finished report is in final draft stage. In this specific design, the venturi principle was used to create a vacuum in the rotating member of the capstan by moving a high velocity blast of air through a restricted annular opening where it produces suction through 57 effective 0.063-inch ports by aspiration.

continued - - -

**CONFIDENTIAL**

**CONFIDENTIAL**

U. S. Government

3

8 September 1965

A51-65-3340

Prior to the test series, an exhaustive calibration of the Lamb pressure/vacuum blower, Model I7 11520, was made using the Roots-Connersville flowmeter outlined in the last monthly report. The blower was tested under conditions of both pressure and vacuum, and its capacity was higher in the latter mode of operation. The manufacturer's performance curves were secured so that test measurements could be compared directly with these figures.

Earlier tests had been made on a 3-inch diameter capstan and these are recorded. Subsequent experiments had shown the most efficient diameter to be between 5 and 6 inches and all of these tests were made on a 6-inch capstan. The first of the series of evaluative runs determined the most efficient gap width in the venturi to produce the highest vacuum attainable with the blower, since velocity is a function of gap width which in turn controls vacuum. The break in the curve occurred between 6 and 7 mils and the results were displayed graphically and tabularly.

The second of the series of tests proved that the capstan configuration was not sensitive to changes in the number of exposed orifi and, thus, did not require baffling to cut off suction in the open portion of its lower periphery. A number of tests were run with the blower in both its vacuum and also its positive-pressure mode, to determine maximum torque attainable with four different widths of film, 70mm, 5, 6.6 and 9-1/2-inch. Capstan speed was constant at 17 rpm. Results indicated that, while either mode was operable, higher torques were obtained with the blower operated as a vacuum pump.

Since atmospheric pressure operating on the outer surface of the film is thought to be almost totally responsible for cohesion between the film and the capstan, higher torque readings would be expected for the wider films. This was not the case. The 70mm film gave the highest, 72-inch-pounds, of the series and an explanation for this anomaly was advanced. The completed report is in its final form awaiting only a few illustrations and a mathematical analysis of the findings.

## 2. Air Bearing (Tunnel)

The experimental evaluation of the Tunnel-Type Air Intertank Transfer Bearing has been completed, and the report is in final draft form. As with the capstan report, some illustrations and a mathematical analysis remain to complete the package.

continued - - -

**CONFIDENTIAL**

**CONFIDENTIAL**

U. S. Government

4

8 September 1965  
A51-65-3340

## 3. Rotary Air Bearing.

Feasibility studies for a self powered air bearing were conducted using the air bearing test bed referred to in Report 974-012-1, Figures 4, 5 and 6. The first setup employed 4-4 inch diameter, four blades fans, 2 left hand in tandem and 2 right hand in tandem, each pair installed at opposite ends so that the air blast from each was directed into the bearing area proper. The bearing area was 4-1/2 inch diameter 10-1/2 inch long cylinder fabricated of 0.025 thick aluminum sheet with 0.040 dia. perforations evenly distributed over approximately 29 percent of its area. The bearing was first run at 3450 R.P.M. and it was immediately apparent that even if the fans were turned up to their maximum of 6200 R.P.M., that there would be insufficient pressure to support a significant load.

The next test was run with a pair of blower wheels installed within the bearing area. These blower wheels are of the squirrel cage configuration, 3.8 inches in diameter and 2-1/2 inches long with one solid end forming the supporting plate and the hub, the normal direction of flow being axial through the open end and exhausting radially. It had been noted that these fans tended to have a higher radial delivery at the back or closed end. Therefore, as expected, with the fans mounted back to back in the center of the bearing, a much higher cushion existed at the center. At 3450 R.P.M., the 9-1/2 inch film loop immediately slid off to one side. The fans were then moved outward in increments of 3/4 of-an-inch to observe the effect upon the distribution of pressure under the film, the idea being that a pressure gradient increasing from the center of the bearing would provide the desirable valley which would cause the film to stay (track) on center. This procedure produced the desired results with the exception that as the fans were moved outward, there was no air pressure to support the narrowest film (70mm) which was tested at this speed.

A second series of test runs were made with the same wheels at 5800 R.P.M., the bearing load capability increasing quite faithfully as the square of the velocity. Even at this higher R.P.M., there was insufficient air pressure to support the 70mm film. To overcome this, 2-2-1/2 inch dia. x .97 inches long blower wheels were installed 1/2 inch apart back to back in the center area of the bearing, between the two 2.8 inch diameter wheels. At the same time a 4-1/2 inch O.D. washer with an I.D equal to the intake diameter of the larger wheels was installed at each end of the perforated cage. The purpose of these

continued - - -

**CONFIDENTIAL**

**CONFIDENTIAL**

U. S. Government

5

8 September 1965  
A51-65-3340

washers was to prevent air from escaping from under the cage at each end, thereby causing sufficient air pressure at the ends of the bearing to keep the 9-1/2-inch film from wandering.

The results of this final setup were very encouraging. The 70mm film now lifted to a cushion depth of approximately 1/16 of-an-inch with a weight of 0.15 lbs.; the 5-inch film supported 0.40 lbs., the 6.6-inch film, 0.84 lbs., and the 9-1/2-inch tracked very well, returning immediately to center when manually offset. It seemed reasonable to assume that the 9-1/2-inch film would track equally well if there were more length to the bearing so that there would be more radial air flow from within at each end of the 9-1/2-inch width. To accomplish a similar effect, an edge flange approximately 4-inches in length, and 1/4-inch high, was installed at both ends at the top center of the bearing. The flanges acted as aerodynamic "fences" which restrained the air exhausting from under the film edge in this area. The "fences" brought about the desired results. The 9-1/2-inch film now tracked exceedingly well, returning to a central position when manually moved against either of the flanges.

Numerous flow and pressure tests were made of this final setup, the results of which will be fully covered in the final report.

#### 4. Sensitometric Studies

##### Problem of Uniform Processing.

A literature survey conducted earlier in the program to determine the best possible method of agitation during processing, revealed that extensive investigative effort has been devoted to the subjects of time and temperature, but the problem of agitation has been less broadly explored, although a great deal of thought has been put into devising special agitation methods such as spray, nitrogen burst, and rocking trays. All these methods employ some means of consistent movement of the processing solution, to remove the unwanted by-products that diffuse from the emulsion during development. Good processing may be summarized as a situation in which every exposed silver halide grain has an equal probability of becoming developed.

1. The developer must diffuse into the entire depth of the emulsion at the same rate.

continued - - -

**CONFIDENTIAL**

**CONFIDENTIAL**

U. S. Government

6

8 September 1965

A51-65-3340

2. The reaction products of development should diffuse from the area of development to allow adsorption of fresh developer so that reduction of the silver halide can continue.

3. The reaction products should be dispersed into the bulk developer as soon as they appear on the emulsion surface.

With these known facts in mind, many methods of agitation were evaluated that would best produce good consistency and reproducibility, especially when high processing temperature and short processing time are involved.

During the first phase of this project, a newer instrument was constructed which provided even better reproducibility. This system which is a modified version of PH 2.5 19602 in which the oscillating movements are performed mechanically, was utilized throughout this phase. Many repetitive tests were made to meet the rigid standards adopted for this project. Gammas were required to be held to a tolerance of  $\pm 0.10$ .

Current tests are being conducted to provide the photographic technician with a complete cross section of gammas, or family of curves. Using this family of curves which will consist of 3 curves for each emulsion (4400, 4401, and 4404), the operator may select any gamma that will best suit the subject matter being processed over the wide range of time-temperature combinations, with the resultant effects upon resolution, fog, speed, and granularity.

The modified version of PH 2.5 1960, was again utilized to produce a time-gamma curve for each emulsion investigated. Starting with the control of 68°F. with a processing time of 8, 5, 3 and 2 minutes which indicated that gamma infinity can be reached in 5 minutes at 68°F.

In producing this time-gamma curve, it was noted that a considerable overlapping effect occurred, indicating a need for a tighter gamma control, beyond the capability of this apparatus to achieve.

In order to separate the overlapping effect, a gamma tolerance of  $\pm 0.05$  or less is necessary. In order to obtain this tolerance a search for suitable off-the-shelf equipment was made, with the result that a  Color Processor was selected as having a good potential for this purpose.

continued- - -

**CONFIDENTIAL**

CONFIDENTIAL

U. S. Government

7

8 September 1965

A51-65-3340

25X1

5. Evaluation of the [ ] Color Processor as a High-Temperature Sensitometric Processor

This Processor is a new motorized drum processor for rapid processing of 8 x 10 and 11 x 14-inch color prints on Kodak Ektacolor Professional Paper. This processor was primarily designed to process Ektacolor Prints and since the color processing requires stringent control, it was believed that it would produce the rigid standards of  $\pm 0.05$  or less gamma control necessary to satisfy this program.

The film samples were held stationary against the rotating drum which constantly picks up and transfers fresh solution to the emulsion with vigorous agitation. A small hinged tray receives the chemical or water in proper sequence. The change from one processing solution to another is made by tilting the tray, rinsing it, and refilling with new solution. Uniform processing temperatures were maintained by circulating thermostatically controlled water. Through the interior of the drum. The processing solutions were automatically controlled to  $\pm 1/20^{\circ}\text{F}$ .

The sensitometric results produced by the drum processor at the 8 min.,  $68^{\circ}\text{F}$ . level, were very satisfactory. Gamma tolerances of  $\pm 0.03$  were maintained from one film sample to another. However, at the 15 second,  $118^{\circ}\text{F}$ . level, the gamma tolerance widened to an unexceptable  $\pm 0.15$ , which was caused by the decrease in viscosity of the developer as the temperature was increased. This loss in viscosity produced a very thin meniscus over the drum surface. The weight of the film being processed was enough to permit the film sample to drag on the surface of the drum resulting in a streaking effect. Since the corrective measures necessary to overcome this effect were beyond a simple change to the processor, this method of sensitometric processing has been reluctantly abandoned.

As an alternative to the procurement and modification of an off-the-shelf item of equipment, a relatively simple concept for a sensitometric processor was conceived, and a mock-up model built as shown in the enclosed photograph. This processor consists briefly of a balance arm on the end of which is a rotating wheel to which the film sample is attached. Three small tanks, immersed in a temperature controlled bath of water, are provided for the processing solutions. By lifting the arm, the wheel can be lowered into the solutions for the required time of immersion. The trays are pulled forward to bring the required solution into position under the wheel at the time of change.

CONFIDENTIAL



CONFIDENTIAL

U. S. Government

8

8 September 1965  
A51-65-3340

Tests are now in progress to evaluate this equipment, which if successful in holding the required gamma tolerance, will be manufactured for use on this program. This requirement illustrates the lack of suitable equipment in this field.

Funds expended during the reporting period are approximately

25X1

If you should have any questions or desire further information, please do not hesitate to contact us.

Very truly yours,



25X1

MCM:IGR:ml

CONFIDENTIAL

☐ SECRET

Approved For Release 2002/07/22 : CIA-RDP78B04747A003200020026-4

☒ CONFIDENTIAL

☒ UNCLASSIFIED

#997604

CONTRACT INSPECTION REPORT		CONTRACT NO.	TASK NO.		
TO: ENGINEERING SECTION/CB/PD/OL		<div>13 September 1965</div>	INSPECTION REPORT NO. (If final, so state) <b>I</b>		
NAME OF CONTRACTOR		ESTIMATED COMPLETION DATE <b>31 December 1965</b>			
TYPE OF COMMODITY OR SERVICE <b>Film Processor Development Program</b>					
THE CONTRACTOR IS ON SCHEDULE <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO		THE CONTRACTOR WILL PROBABLY REMAIN WITHIN ALLOCATED FUNDS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO IF ANSWER IS "NO" ADVISE RECOMMENDATION AND/OR ACTION OF SPONSORING OFFICE, ON REVERSE HEREOF. IF KNOWN, INDICATE MAGNITUDE OF ADDITIONAL FUNDS INVOLVED.			
PER CENT OF WORK COMPLETED - <b>30%</b>					
PER CENT OF FUNDS EXPENDED - <b>30%</b>					
HAS AN INTERIM REPORT, FINAL REPORT, PROTOTYPE, OR OTHER END ITEM BEEN RECEIVED FROM THE CONTRACTOR DURING THE PERIOD? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO (If yes, give details on reverse side.)					
HAS GOVERNMENT-OWNED PROPERTY BEEN DELIVERED TO CONTRACTOR DURING THIS PERIOD? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO (If yes, indicate items, quantity, and cost on reverse side.)					
INCENTIVES					
IS THIS AN INCENTIVE CONTRACT <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO IF YES, CHECK TYPE <input type="checkbox"/> COST <input type="checkbox"/> PERFORMANCE <input type="checkbox"/> DELIVERY		NOTE: USE REVERSE SIDE FOR COMMENTS. FINAL REPORT MUST CONTAIN INCENTIVE EVALUATION.			
OVERALL PERFORMANCE OF CONTRACTOR					
1. <input type="checkbox"/> OUTSTANDING 3. <input type="checkbox"/> ABOVE AVERAGE 5. <input type="checkbox"/> BELOW AVERAGE 7. <input type="checkbox"/> UNSATISFACTORY					
2. <input type="checkbox"/> EXCELLENT 4. <input checked="" type="checkbox"/> AVERAGE 6. <input type="checkbox"/> BARELY ADEQUATE					
IF OVERALL PERFORMANCE OF CONTRACTOR IS UNSATISFACTORY OR BARELY ADEQUATE, INDICATE REASONS ON REVERSE SIDE.					
RECOMMENDED ACTION					
<input checked="" type="checkbox"/> CONTINUE AS PROGRAMMED <input type="checkbox"/> WITHHOLD PAYMENT PENDING SATISFACTORY PERFORMANCE					
<input type="checkbox"/> TERMINATE <input type="checkbox"/> OTHER (Specify)					
IF TERMINATION IS RECOMMENDED OR IF THIS IS A FINAL REPORT PUT COMMENTS ON REVERSE IN NARRATIVE FORM ON CONTRACTOR'S PERFORMANCE AND CERTIFY THAT ALL DELIVERABLE ITEMS UNDER THE CONTRACT HAVE BEEN RECEIVED. THESE INCLUDE, WHERE APPLICABLE, THE FOLLOWING:					
ITEM	REC'D	DOES NOT APPLY	ITEM	REC'D	DOES NOT APPLY
PROTOTYPES			MANUALS		
DRAWINGS AND SPECIFICATIONS			FINAL REPORT		
PRODUCTION AND/OR OTHER END ITEMS			SPECIAL TOOLING		
			OTHER GOVERNMENT PROPERTY		
DATE OF LAST CONTACT WITH CONTRACTOR <b>3 September 1965</b>					
SIGNATURE					
INSPECTOR					

Approved For Release 2002/07/22 : CIA-RDP78B04747A003200020026-4

☐ SECRET

Approved For Release 2002/07/22 : CIA-RDP78B04747A003200020026-4

☒ CONFIDENTIAL

☐ UNCLASSIFIED

NARRATIVE REPORT

☒ INTERIM

☐ FINAL

This contract, a continuation of Contract ☐ has been satisfactory as far as progress is concerned. Some reorientation was necessary at the inception of this phase, which has been accomplished. Seven basic investigative tasks have evolved as a result of the redefinition, five of which are a follow-on of the original contract.

25

☐ UNCLASSIFIED

☒ CONFIDENTIAL

☐ SECRET

Approved For Release 2002/07/22 : CIA-RDP78B04747A003200020026-4